









DIN - 公制

CA	A-50	CE	A-50	CF	A-51
					
24°锥内螺纹 - 轻系列 - O形圈 - 直接头		24°锥内螺纹 - 轻系列 - O形圈 - 45°接头		24°锥内螺纹 - 轻系列 - O形圈 - 90°接头	

SAE

01	A-51	06	A-52	08	A-52	68	A-53
							
NPTF外螺纹 - 直接头		JIC 37°锥内螺纹 - 直接头		SAE 45°锥 - 内螺纹 - 直接头		JIC 37°/SAE 45°双锥 - 内螺纹 - 直接头	

ORFS

JC	A-53
	
ORFS内螺纹 - 直接头 - 短型	

软管, 接头及设备

A

硬管接头及设备

B


快换接头

C

其他产品

D

A 软管, 接头及设备



1CA26


公制24°锥内螺纹带O形圈 - 轻系列 - 直接头
ISO 12151-2-SWS-L – DKOL

# 型号	🌀 螺纹 公制		● 软管内径 I.D.		A mm	B mm	W mm
			inch	mm			
1CA26-6-4	6	M12x1.5	3/16	5.0	40	20	14
1CA26-8-4	8	M14x1.5	3/16	5.0	41	21	17
1CA26-10-5	10	M16x1.5	1/4	6.3	41	20	19
1CA26-10-6	10	M16x1.5	5/16	8.0	41	20	19
1CA26-12-6	12	M18x1.5	5/16	8.0	41	21	22
1CA26-12-8	12	M18x1.5	13/32	10.0	41	21	22
1CA26-15-8	15	M22x1.5	13/32	10.0	42	21	27
1CA26-18-10	18	M26x1.5	1/2	12.5	46	23	32
1CA26-18-12	18	M26x1.5	5/8	16.0	46	23	32
1CA26-22-12	22	M30x2	5/8	16.0	48	25	36
1CA26-28-16	28	M36x2	7/8	22.0	54	28	41
1CA26-28-20	28	M36x2	1-1/8	29.0	60	34	41
1CA26-35-20	35	M45x2	1-1/8	29.0	56	29	50
1CA26-35-24	35	M45x2	1-3/8	35.0	62	34	50
1CA26-42-24	42	M52x2	1-3/8	35.0	59	31	60

B 硬管接头及设备

1CE26

公制24°锥内螺纹带O形圈 - 轻系列 - 45°接头
ISO 12151-2-SWE 45°-L – DKOL 45°



# 型号	🌀 螺纹 公制		● 软管内径 I.D.		A mm	B mm	E mm	W mm
			inch	mm				
1CE26-10-6	10	M16x1.5	5/16	8.0	66	45	17	19
1CE26-12-6	12	M18x1.5	5/16	8.0	66	45	17	22
1CE26-12-8	12	M18x1.5	13/32	10.0	59	39	17	22
1CE26-15-8	15	M22x1.5	13/32	10.0	60	39	17	27
1CE26-18-10	18	M26x1.5	1/2	12.5	69	46	21	32
1CE26-18-12	18	M26x1.5	5/8	16.0	73	50	22	32
1CE26-22-12	22	M30x2	5/8	16.0	77	55	26	36
1CE26-28-16	28	M36x2	7/8	22.0	103	76	33	41

C 快换接头

D 其他产品


样本尺寸仅供参考, 请以实际产品尺寸为准。

1CF26

公制24°锥内螺纹带O形圈 - 轻系列 - 90°接头

ISO 12151-2-SWE-L – DKOL 90°

# 型号	🌀 螺纹 公制		● 软管内径 I.D.		A mm	B mm	E mm	📐 W mm
			inch	mm				
1CF26-8-4	8	M14x1.5	3/16	5.0	48	28	29	17
1CF26-10-5	10	M16x1.5	1/4	6.3	55	36	29	19
1CF26-10-6	10	M16x1.5	5/16	8.0	55	34	31	19
1CF26-12-6	12	M18x1.5	5/16	8.0	56	35	35	22
1CF26-12-8	12	M18x1.5	13/32	10.0	51	30	31	22
1CF26-15-8	15	M22x1.5	13/32	10.0	58	38	41	27
1CF26-18-10	18	M26x1.5	1/2	12.5	57	34	38	32
1CF26-18-12	18	M26x1.5	5/8	16.0	69	46	45	32
1CF26-22-12	22	M30x2	5/8	16.0	78	55	47	36
1CF26-28-16	28	M36x2	7/8	22.0	95	68	71	41
1CF26-28-20	28	M36x2	1-1/8	29.0	117	90	81	41
1CF26-35-20	35	M45x2	1-1/8	29.0	117	90	77	50
1CF26-35-24	35	M45x2	1-3/8	35.0	117	89	79	50




10126

NPTF外螺纹 - 直接头


SAE J476A / J516 – AGN

# 型号	🌀 螺纹 NPTF	● 软管内径 I.D.		A mm	B mm	📐 H inch
		inch	mm			
10126-2-4	1/8x27	3/16	5.0	42	20	7/16
10126-4-4	1/4x18	3/16	5.0	48	26	9/16
10126-4-5	1/4x18	1/4	6.3	48	26	9/16
10126-4-6	1/4x18	5/16	8.0	48	26	3/4
10126-6-6	3/8x18	5/16	8.0	48	26	11/16
10126-6-8	3/8x18	13/32	10.0	48	26	11/16
10126-8-8	1/2x14	13/32	10.0	54	33	7/8
10126-8-10	1/2x14	1/2	12.5	57	33	7/8
10126-12-12	3/4x14	5/8	16.0	59	35	1-1/16
10126-16-16	1x11-1/2	7/8	22.0	66	40	1-3/8
10126-20-20	1-1/4x11-1/2	1-1/8	29.0	72	45	1-3/4
10126-24-24	1-1/2x11-1/2	1-3/8	35.0	76	49	2
10126-32-32	2x11-1/2	1-13/16	46.0	87	55	2-1/2



样本尺寸仅供参考，请以实际产品尺寸为准。

A 软管, 接头及设备



10626 JIC 37°锥内螺纹 - 直接头


ISO 12151-5-SWS-DKJ

# 型号	🌀 螺纹 UNF		● 软管内径 I.D.		A mm	B mm	⬡ H inch
	inch	mm	inch	mm			
10626-6-6	3/8	9/16x18	5/16	8.0	45	23	11/16
10626-6-8	3/8	9/16x18	13/32	10.0	52	30	11/16
10626-12-12	3/4	1-1/16x12	5/8	16.0	43	19	1-1/4
10626-16-16	1	1-5/16x12	7/8	22.0	47	21	1-1/2
10626-20-20	1-1/4	1-5/8x12	1-1/8	20.0	50	24	2
10626-24-24	1-1/2	1-7/8x12	1-3/8	35.0	53	25	2-1/4
10626-32-32	2	2-1/2x12	1-13/16	46.0	64	32	2-7/8

B 硬管接头及设备

10826 SAE 45°锥内螺纹 - 直接头

SAE J516



# 型号	🌀 螺纹 UNF		● 软管内径 I.D.		A mm	B mm	⬡ H inch
	inch	mm	inch	mm			
10826-6-6	3/8	5/8x18	5/16	8.0	47	25	3/4
10826-10-8	5/8	7/8x14	13/32	10.0	56	34	1
10826-10-10	5/8	7/8x14	1/2	12.0	54	30	1
10826-12-12	3/4	1-1/16x14	5/8	16.0	56	32	1-1/4

C 快换接头

D 其他产品


样本尺寸仅供参考, 请以实际产品尺寸为准。

16826

JIC 37° / SAE 45° 双锥 - 内螺纹 - 直接头

ISO 12151-5-SWS-DKJ

# 型号	🌀 螺纹 UNF		● 软管内径 I.D.		A mm	B mm	⬡ H	
	inch	mm	inch	mm			inch	mm
16826-4-4	1/4	7/16x20	3/16	5.0	42	20	9/16	
16826-4-5	1/4	7/16x20	1/4	6.3	48	26	9/16	
16826-4-6	1/4	7/16x20	5/16	8.0	39	17	9/16	
16826-5-5	5/16	1/2x20	1/4	6.3	45	23	5/8	
16826-8-6	1/2	3/4x16	5/16	8.0	56	34	7/8	
16826-8-8	1/2	3/4x16	13/32	10.0	49	27	7/8	
16826-8-10	1/2	3/4x16	1/2	12.5	60	36	7/8	
16826-10-10	5/8	7/8x14	1/2	12.5	55	31	1	
16826-10-12	5/8	7/8x14	5/8	16.0	61	37	1	




1JC26

ORFS内螺纹 - 直接头 - 短型

ISO 12151-1 - SWSA / SAE J516 - ORFS

# 型号	🌀 螺纹 UNF		● 软管内径 I.D.		A mm	B mm	C mm	⬡ H W	
	inch	mm	inch	mm				inch	mm
1JC26-4-4	1/4	9/16x18	3/16	5.0	42	20	8	9/16	11/16
1JC26-6-6	3/8	11/16x16	5/16	8.0	43	21	9	11/16	13/16
1JC26-8-8	1/2	13/16x16	13/32	10.0	45	23	11	13/16	15/16
1JC26-12-12	3/4	1-3/16x12	5/8	16.0	54	30	14	1-1/8	1-3/8
1JC26-16-16	1	1-7/16x12	7/8	22.0	61	34	14	1-3/8	1-5/8
1JC26-20-20	1-1/4	1-11/16x12	1-1/8	29.0	62	35	15	1-7/8	1-7/8



样本尺寸仅供参考，请以实际产品尺寸为准。